PIXMA GM2040 **HIGH-YIELD BLACK AND** WHITE INK TANK **PRINTING WITH** A LOW COST-**PER-PAGE**

Achieve cost-effective printing at high volumes. Refill with ease using the no-squeeze, mess-free bottles and benefit from high yields of up to 18,000 black pages from 3 black ink bottles¹ for smooth production, uncompromised quality and a low cost-per-page.









- Top productivity
- Flexible connectivity
- High-speed quality
- Business savvy







Smartphone Copy



Connectivity



PRODUCT RANGE



PIXMA GM2040



PIXMA G5040



PIXMA G6040





Live for the story

¹ Page yield is the estimated value based on Canon individual test method using the ISO/IEC 19752 monochrome chart and continuous printing simulation with the replacement after initial setup.

TECHNICAL SPECIFICATIONS

GENERAL SPECIFICATIONS Functions

PRINTER SPECIFICATIONS Print Resolution Print Technology

Mono Print Speed Colour Print Speed (with optional colour cartridge) Two Sided Printina

CARTRIDGES AND YIELDS Standard Ink Cartridaes Optional Colour Ink Cartridges Cartridge Yield (Plain paper)

PAPER SUPPORT Paper Types

Maximum Paper Input

Paper Sizes

Paper Weight

Interface Type - PC / Mac

Interface Type - Other

SOFTWARE Supported Operating Systems

Supported Mobile Systems Minimum System Requirements

Software Included

Wi-Fi, Ethernet, Black & White Print

Up to 600^[1] x 1200 dpi 1 FINE Cartridge (Black) with Optional Colour Cartridge Refillable ink tank printer Approx, 13.0 ipm Approx. 6.8 ipm [2]

Auto Duplex Print (A4, A5, B5, Letter - Plain Paper)

GI-40 <PGBK> CL-541 CL-541XL A4 monochrome documents printing^[3] Black: 6,000 pages Colour (CL-541): 180 pages ^[4] Colour (CL-541XL): 400 pages ^[4] * Estimated supplemental yield

Plain Paper High Resolution Paper (HR-101N) Envelope Rear Tray: Max. 100 sheets (plain paper) Cassette: Max. 250 sheets (plain paper) Rear Tray: A4, A5, B5, LTR, LGL Envelopes(DL, COM10), Card Size(91 x 55mm) [Custom size] width 55mm - 215.9 mm, length 89mm - 676mm Cassette: A4, A5, B5, LTR [Custom size] width 148.0 mm - 215.9 mm, length 210mm - 297mm Rear Tray/Cassette: Plain paper: 64 - 105 g/m²

Hi-Speed USB (B Port) Ethernet: 10/100Mbps (auto switchable) Wi-Fi: IEEE802.11 b/g/n Wi-Fi Security: WPA-PSK, WPA2-PSK, WEP, Administration password Wireless LAN Frequency Band: 2.4GHz Canon PRINT Inkiet/SELPHY app Canon Print Service Plugin (Android) Wireless Direct Access Point Mode Windows 10, Windows 8.1, Windows 7 SP1

Operation can only be guaranteed on a PC with pre-installed Windows 7 or later. Printer driver and IJ Network Device Setup Utility are available with following OS. Windows Server 2008 R2 SP1、Windows Server 2012 R2、Windows Server 2016 iOS, Android (via Canon PRINT Inkjet/SELPHY app) Windows: 2.0GB or more

Note: for bundled software installation. The necessary amount of hard disk space required. Display: 1024 x 768 XGA

Printer Driver IJ Printer Assistant Tool

PHYSICAL FEATURES Weight Dimensions (W x D x H)

Acoustic Noise Levels Operating Temperature Operating Humidity Power Source Power Consumption

Typical Electricity Consumption (TEC)

Footnotes

1) Ink droplets can be placed with a minimum pitch of 1/4800 inch

0.1kWh^[7]

approx. 6.0kg

5-35°C

approx. 403 x 369 x 166 mm approx. 52.0dB(A)^[5]

AC 100-240V 50/60Hz

Off: Approx. 0.3W

10-90%RH (no dew condensation)

Standby (connected to PC via USB): Approx. 0.8W

Standby (all ports connected): Approx. 1.6W Time to enter Standby mode: 1min 29sec

Printing (USB connection to PC): Approx. 13W [6]

- [2] A4 document print speed on plain paper is measured based on average of ESAT in Office Category Test of ISO/IEC 24734 standard. ^[3] Page Yield is the estimated value based on Canon individual test method using
- the ISO/IEC 19752 monochrome chart and continuous printing simulation with the replacement after initial setup.
- (4) Print colour document with optional colour cartridge. This product is a monochrome inkjet printer.
- Although colour printing can be done by purchasing a compatible colour cartridge, quickly using up the ink in the installed cartridge is recommended. Once the installed colour cartridge is empty, please replace with the contact protector or a new colour cartridge.
- ⁽⁵⁾ Plain Paper(A4, B/W). Acoustic Noise is measured based on ISO7779 standard.
 ⁽⁶⁾ Print: When printing ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.
- 71 Typical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit will be constantly switched among operational mode, sleep mode, and power-off mode for 5 days, and that it will be either in sleep or power-off mode for the remaining 2 days within the same week. The TEC value of this product is calculated by Canon or accord using TEC measurement procedure regulated in International ENERGY STAR Program.

Standard disclaimers

All specifications subject to change without notice. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canon-europe.com/ink/vield

All brand and product names are trademarks of their respective companies. Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

What's in the box?

- Single-function black and white refillable ink tank printer - PIXMA GM2040
- 3 high-yield ink bottles (3x Black)
- Power cord
- Setup CD-ROM
- Manuals and other documents

Canon Inc. canon.com Canon Europe canon-europe.com English edition Canon Europa NV 2019



PIXMA GM2040